


PIN CONFIGURATION



SP629A

ELECTRICAL CHARACTERISTICS (Notes 1, 2, 3, 5 and 7)

Standard Conditions: $V_{CC} = 5.0V$, $T_A =$ Operating Temperature Range (Unless Noted)

CHARACTERISTIC	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Output Voltage "1" Level	$I_{out} = -200\mu A$, Driven Input	3.8			V
"0" Level	$I_{out} = 20mA$, Driven Input			0.6	V
	$I_{out} = 12.5mA$ Driven Input			0.4	
Input Current input high S_D, R_D , clock	$V_{in} = 5.0V$			25	μA
S_C, R_C	$V_{in} = 5.0V$			25	μA
input low S_D, R_D, S_C, R_C	$V_{in} = 0.6V$			-2.5	mA
Clock Effective Capacitor	$V_{in} = 5.0V, T_A = 25^\circ C$		75	10	pF
Power Supply Current	$V_{in} = 5.0V, T_A = 25^\circ C$			10	mA
Turn on Delay clocked	See Test Figure 1, $T_A = 25^\circ C$			100	ns
direct	See Test Figure 2, $T_A = 25^\circ C$			100	ns
Turn off Delay clocked	See Test Figure 1, $T_A = 25^\circ C$			100	ns
direct	See Test Figure 2, $T_A = 25^\circ C$			100	ns
Fan-out -To sink loads (2.5mA/load)				8	
-To source loads (180 μA /load)				1	

Typical Values are for $T_A = 25^\circ C$. See Page 3 for Notes.

